



Performance through Quality

Series Stationary

Single & Two Stage

230 V 1 Phase / 400 V 3 Phase



Single Stage – Two Cylinder Models

A10 / 60 – A20 / 210

Features

- Industrial duty rated
- British air receivers
- High efficiency air pumps
- Auto stop / start
- Motors heavy duty IP55
- Low vibration levels
- Deep finned cast iron cylinder

Two Stage – Two Cylinder Models

A22 / 210 - A50 / 250



British Built



Two Stage – Four Cylinder Models

A70/350 - A100 / 350

Features

- Balanced flywheel / multi blade fan for efficient cooling
- Minimum maintenance cost
- Easy installation
- Thermal protection to all motors
- Star-delta starters fitted to 10 / 15 / 20 HP units
- Spares & service nationwide
- Exports worldwide





SERIES STATIONARY

SINGLE & TWO STAGE

230v 1 Phase/400v 3 Phase

Professionals in Compressed Air

MODEL	DISPLACEMENT		FAD		MAX PRESSURE PSI - BAR	MOTOR HP - KW	PHASE	RECEIVER LITRES	DIMENSIONS			KG
	CFM	LTS	CFM	LTS					L	W	H	
A6/50-1	6.0	170	3.6	102	125 - 8.5	1.5 - 1.1	1	50	1085	340	720	49
A10/50-1	9.0	255	5.4	255	150 - 10.0	2.0 - 1.5	1	50	1085	340	720	55
A10/110-1	9.0	255	5.4	255	150 - 10.0	2.0 - 1.5	1	110	1320	370	770	75
A15/110-1	15.0	425	10.3	292	150 - 10.0	3.0 - 2.2	1	110	1320	370	775	84
A15/160-1	15.0	425	10.3	292	150 - 10.0	3.0 - 2.2	1	160	1580	380	880	94
A18/160-1	16.0	453	12.0	339	150 - 10.0	3.0 - 2.2	1	160	1580	390	890	97
A18/210-1	16.0	453	12.0	339	150 - 10.0	3.0 - 2.2	1	210	1640	460	930	125
A20/210-1	20.0	566	13.4	372	150 - 10.0	4.0 - 3.0	1	210	1640	460	930	131
A6/50-3	6.0	170	3.6	102	125 - 8.5	1.5 - 1.1	3	50	1085	340	720	49
A10/50-3	9.0	255	5.4	255	150 - 10.0	2.0 - 1.5	3	50	1085	340	720	55
A10/110-3	9.0	255	5.4	255	150 - 10.0	2.0 - 1.5	3	110	1320	370	770	75
A15/110-3	15.0	425	10.3	292	150 - 10.0	3.0 - 2.2	3	110	1320	370	775	84
A15/160-3	15.0	425	10.3	292	150 - 10.0	3.0 - 2.2	3	160	1580	380	880	94
A18/160-3	16.0	453	12.0	339	150 - 10.0	3.0 - 2.2	3	160	1580	390	890	97
A18/210-3	16.0	453	12.0	339	150 - 10.0	3.0 - 2.2	3	210	1640	460	930	125
A23/210-3	22.0	623	15.4	436	150 - 10.0	5.5 - 4.0	3	210	1640	460	1000	155
A25/210-3	25.0	708	18.0	510	150 - 10.0	5.5 - 4.0	3	210	1640	460	1000	163
A26/210-3	26.0	736	20.0	566	150 - 10.0	5.5 - 4.0	3	210	1640	460	1150	174
A30/250-3	30.0	850	22.5	637	150 - 10.0	7.5 - 4.0	3	250	1650	490	1200	213
A50/250-3	42.0	1189	31.5	892	150 - 10.0	10.0 - 7.5	3	250	1650	490	1290	256
A70/350-3	60.0	1699	45.0	1274	150 - 10.0	15.0 - 11.0	3	350	1930	600	1270	354
A100/350-3	80.0	2265	60.0	1699	150 - 10.0	20.0 - 15.0	3	350	1930	600	1340	412

SPECIFICATIONS

E.&O.E. - SPECIFICATIONS ARE SUBJECT TO ALTERATION WITHOUT PRIOR NOTICE.